





Csavarkompresszor APS 15 COMBI DRY X

Product Images



Additional Information

Cikkszám	369015
EAN 13	08712418372311
Hossz (mm)	1850
Width (mm)	820
Height (mm)	1880
Súly (kg)	530.000000
Workload (labor/rest %)	100/0
Motor erő (LE/kW)	15.0 HP / 11.0 kW
Motor efficiency class	IE3
Motor típus	AC
Meghajtás	Direct driven 1:1
Control panel	MAM-860
Elérhető nyelvek	Angol, Holland, Lengyel
Szárító	Igen
Dryer voltage (V)	230
Air Receiver	Igen
Légtartály (l)	500
Galvanized tank	Nem
Maximális nyomás (bar)	10
Szabad levegő szállítás (l/perc)	1410
Szabad levegő szállítás (m3/óra)	84.6
Zajszint dB A 0mm	63
Zajszint dB A 4 mm	43
Cut-in pressure (bar)	6
Plug type	EU
Main air connection (")	3/4

Minimum környezeti hőmérséklet (°C)	10
Maximum ambient temperature (°C)	45
Oilfree	Nem
Fokozatok	1
Kezdet	Y-Δ
Hálózati feszültség (V)	400 V / 50 Hz / 3 Ph
Variable speed (IVR)	Nem

Leírás

The APS 15 Combidry X is a 11 kW direct-driven screw compressor with a fixed speed and a output of 1410 liters per minute. Due to the compact design, this machine takes up little space, but it does have a 500 liter compressed air boiler and a cooling dryer. The direct drive ensures a 1 on 1 transfer from the electric motor to the screw block, so that no losses occur. A large screw block ensures a high airflow at a low speed. The most important parameters can be read and adjusted on the display of the controller. A large oil cooler with fan, which temperature is switched, ensures proper cooling without unnecessary energy consumption. The machine has been carefully designed so that there are fewer maintenance-sensitive parts. The service interval of 3,000 hours also ensures lower maintenance costs. With the right filtering, also suitable for damage repair companies but also for controlling sorting machines in the horticultural sector, for example.

X series Screw compressors

By continuously investing in the development of our products, the Airpress Group presents a new series of screw compressors. The screw compressors are available from 5.5 kW to 37 kW. The APS X series is available in two versions: controlled at a fixed speed or speed. Machines of 15 kW are also available with a two-stage screw block. These versions have an increased performance with the same power consumption as a single-stage version. Depending on demand, these machines are available as a separate unit, mounted on a tank or mounted on a tank and equipped with a compressed air dryer. Compressors of the X series are characterized by a new generation of screw blocks. The direct drive avoids losses due to the transmission. Reliable and efficient, easy-to-use screw compressors ensure trouble-free operation at minimal costs. Equipped with a modern control panel, you can constantly monitor the screw compressor and change parameters if necessary. With Smartcontrol

Feedback verzenden

Geschiedenis

Opgeslagen

Community

